

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/044709 A1

(51) International Patent Classification⁷: **B66B 5/04**

(21) International Application Number:
PCT/US2003/031551

(22) International Filing Date: 7 October 2003 (07.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **OTIS ELEVATOR COMPANY** [US/US]; Ten Farm Springs Road, Farmington, CT 06032 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **OH, Jae-Hyuk** [KR/US]; 5 Clearbrook Drive, Tolland, CT 06084 (US). **MILLER, Robin, Mihekun** [US/US]; 125 Burbank Road, Ellington, CT 06029 (US). **PERUGGI, Richard, E.** [US/US]; 153 Hurlburt Street, Glastonbury, CT 06033

(US). **WAN, Samuel** [US/US]; 6 Kerr Farm Road, Simsbury, CT 06070 (US). **COONEY, Anthony** [US/US]; 211 Coppermine Road, Unionville, CT 06085 (US). **BACELLAR, Adriana** [BR/US]; 44 Grandview Drive, Glastonbury, CT 06033 (US). **PENG, Peie-Yuan** [—/US]; 7 Rothe Lane, Ellington, CT 06029 (US).


(74) Agent: **LABA, Kerrie, A.**; Carlson, Gaskey & Olds, 400 West Maple Road, Suite 350, Birmingham, MI 48009 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: REMOTELY RESETTABLE ROPELESS EMERGENCY STOPPING DEVICE FOR AN ELEVATOR



(57) Abstract: A brake mechanism (10) for an elevator (2) is activated in response to an electronic control signal to prevent movement of an elevator car (16) under predetermined conditions. The brake mechanism is preferably a safety mechanism (10) and does not require a governor sheave, a governor rope, or a tension sheave. The safety mechanism in one disclosed example utilizes a solenoid actuator (22b) and an electric motor (40) and gear box assembly (42) to move safety wedges (18) into engagement with a guide rail (20) to stop the elevator car (16). The safety wedges (18) are held in a non-deployed position during normal elevator operation. If there is a power loss or if elevator car speed exceeds a predetermined threshold, an electronic control signal activates the safety mechanism (10) causing the solenoid to release, which causes the safety wedges (18) move in a direction opposite to that of a safety housing (12) mounted for movement with the elevator car (16). Angled surfaces of the safety housing (12) force the safety wedges (18) into engagement with the guide rail (20). The safety mechanism (10) can be selectively reset from a remote location.

Best Available Copy

WO 2005/044709 A1



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.